

(11)Publication number:

2002-050607

(43)Date of publication of application: 15.02.2002

(51)Int.CI.

H01L 21/304 C23G 1/02 C23G 1/14 H01L 21/306

(21)Application number: 2000-236082 (22)Date of filing:

03.08.2000

(71)Applicant: KAIJO CORP

(72)Inventor:

OKANO KATSUICHI


ECHIGO TOMOMI OSAWA TADAYASU

(54) SUBSTRATE TREATMENT METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a substrate treatment method which can prevent metal impurity ions from attaching, without corroding metallic wirings, etc., in a substrate surface, and can improve the cleanliness level of a substrate by surely removing particle and metal impurities which attach to a recess and a step part generated in a metal wiring.

SOLUTION: A substrate 1 is treated in a first process A for cleaning with organic alkaline treatment liquid, a second process B for cleaning after the first process by means of organic acid treatment liquid and a third process C for cleaning, after the second process by means of ultrasound cleaning fluid oscillated by ultrasonic wave. An organic alkaline treatment liquid and organic acid treatment liquid are nonreactive to a metallic material of a metal wiring of the substrate 1 and can improve the cleanliness level of the substrate 1, by preventing metal impurity ions from attaching, without corroding the metal wrings, etc., of a substrate surface; since it contains complexing agent which forms a complex with particles in a metallic material and metals included in polishing solution, when the substrate 1 is chemomechanically polished.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted

registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

15.08.2000

28.06.2002